

## GSM106 BA PS

Universal GSM gateway and data communication for the supervision management by Vega Cloud with integrated backup battery and power supply.

### BENEFITS



DIRECT ACCESS TO CLOUD

### SIZE

120x101x46 mm

### MAIN FEATURES

- Backup battery management.
- Power supply and battery check, and related failure SMS.
- 220V Power supply.

### TECHNICAL DATA

Maximum Electric current absorbed: 1 A.  
GSM radio module: 850/900/1800/1900 MHz.  
GPRS Radio module: class 12.  
Line interface - ring voltage: 150V eff 25 Hz  
+/-5%.

Communication Interfaces: RS232, RS485,  
CAN BUS.

Installation: fixing on the wall.  
Input voltage: 220Vac to 12Vdc

### CODE

GSM106 BA PS-I: universal GSM gateway with Italian power plug.  
GSM106 BA PS-UK: universal GSM gateway with British power plug 3 poles.



### BENEFITS



DIRECT ACCESS TO CLOUD



APP FOR PROGRAMMING

### SIZE

110x70x25 mm

## GSM300

GSM interface for Vega auto-dialer and data communication for CL24.

### MAIN FEATURES

- Simplified wiring by only one connector.
- Power supply by Auto-Dialer.
- Caller ID visualization.
- SMS management.
- External antenna with magnetic base and 2 m. of wire.
- Remote control of GSM signal level.
- PIN management.
- Data modem for CL24.

### TECHNICAL DATA

GSM radio module: 850/900/1800/1900 MHz.  
GPRS radio module: class 12.